

Parachlorobenzotrifluoride (PCBTf)

TECHNICAL DATA SHEET

Parachlorobenzotrifluoride is used as VOC exempt solvent in many paints, adhesives and coatings. It has a good solubility profile with a mid-range evaporation rate. Parachlorobenzotrifluoride can be used in both Parts A and B of urethanes and epoxies. It is VOC exempt in all 50 States and Canada. It is a stable, non reactive, non corrosive, hydrophobic, low polarity solvent. It will not undergo hydrolysis or dehydrochlorination and does not support combustion.

SALES SPECIFICATIONS & PROPERTIES

<u>PROPERTY</u>	<u>LIMITS</u>
Appearance	Clear liquid
Purity, %	99.00 Minimum
O-Chlorobenzotrifluoride, %	0.20 Maximum
M-Chlorobenzotrifluoride, %	0.50 Maximum
Water, ppm	150 Maximum
PH	5.0 – 7.0
Acidity, ppm	3.0 Maximum
Residue on Evaporation, %	0.0020 Maximum
Specific Gravity	1.33 – 1.35
Color, APHA	20 Maximum

PRODUCT & PACKAGING INFORMATION

PCBTf is available in 55 gallon drums or totes.

CONTACT INFORMATION

ChemCeed LLC
1720 Prosperity Court
Chippewa Falls, WI 54729

Phone 1. 715.726.2300
inquiry@chemceed.com